



30 kW DIESEL GENERATOR

30,000 WATT

60 Hz., 1800 RPM Liquid Cooled

Single Phase, 1.0 Power Factor

Automatic Voltage Regulated

250 Amp - 120 Volt

125 Amp - 240 Volt



GENERATOR FEATURES

High Performance Compact Design

Built in Canada to meet the toughest customers needs. New high performance clean diesel power from a quieter compact design. Power you can depend on for home, commercial or off-grid applications.

Engine

Powered by a Perkins 400 Series Engine. These engines are compact and easy to start. Perkins is known for their exceptional performance and long life. Low fuel consumption and durability make them a popular choice worldwide for power generation. Customers also save on maintenance since the engines require fewer air filter, oil filter and lube oil changes. (Oil changes every 500 hours depending on load factor)

Alternator

Highly reliable industrial class alternator. A popular choice for harsh conditions where clean, stable power is required. Output is electronically voltage regulated to within 1% precision. The brushless design requires no maintenance.

Integrated Fuel Tank

Large capacity fuel tank is located in the base frame of the generator. Easy to read fuel level indicator and 304/316 stainless steel electronic fuel level sensor. In-tank fuel filter provides dual filtration.

Controller

Clear generator instrumentation, protection and control. 150 event logging, fuel level display and alarm, maintenance and exercise clock and much more. The controller is built to withstand severe duty, extreme shock and vibration. Easy to use and configure via front panel buttons. Can be used manually or fully automatic with optional Automatic Transfer Switch or wireless remote control. Accepts additional customer sensors and switched outputs.

Canopy Enclosure - Optional

Weather resistant enclosure is constructed out of galvanized steel and assembled with high strength stainless steel fasteners. Powder coated finish, acoustical sound insulation and chrome plated locks secure the doors from unauthorized access. The generator is designed to be cosmetically appealing while still being able to withstand harsh operating conditions.

All-In-One Generator

Suitable for a wide range of applications from residential emergency standby to off-grid power applications.

Limited Warranty - Aurora 5 YEAR Generator Warranty, Perkins 3000 hours or two year engine warranty (three year core components) Perkins warranty is comprehensive and covers all parts and labour plus miscellaneous items such as the travel costs of engineers to repair the engine. Optional extended warranty also available from Perkins.

OPTIONS

- Canopy Enclosure
- DynaGen TG410 Controller
- Current Sensing
- Key-chain Wireless Remote
- Riser Feet
- Engine Block Heater

- Sub Base Double Wall High Capacity Fuel Tank
- Battery Charger
- Solar Battery Maintainer
- Automatic Transfer Switch
- Leasing and Financing OAC



30 kW DIESEL GENERATOR

Generator Specifications

| | |
|----------------------------------|--|
| Model | AGi30P |
| Type | Diesel |
| Power | 30,000 watts 60 Hz Single Phase 125 amps @ 240 volts AC 250 amps @ 120 volts AC |
| Sound Level (Canopy) | 68 dB @ 23 ft. |
| Dimensions & Weight (Open Frame) | 61"L x 33"W x 44"H 1250 lbs |
| Dimensions & Weight (Canopy) | 73.25"L x 40.25"W x 50"H 1950 lbs |
| Country of Origin | Made in Canada |
| Approvals | CSA SPE-1000 |

Generator Controller

| | |
|---|---|
| DynaGen | TG350 / TG410 (Optional) |
| Operating Voltage | 5.5 to 38VDC continuous. Cranking dropouts to 0 VDC for 50 mS, also meets SAE J1113-11 |
| Standby Current Draw | 50 mA |
| Protection | Reverse battery protected & Overload |
| Operating Temperature | -40 - +158 F |
| Vibration & Shock | Meets or exceeds SAE J1455 |
| Electromagnetic Compatibility | Meets or exceeds MIL-STD-461E Conducted Emissions |
| Configurable Switched Inputs | 5 |
| Configurable Switched Outputs (in addition to fuel & crank) | 4 |
| Warranty | 5 Years |

 **Perkins®**

Diesel Power

Engine Specifications

| | |
|--------------------------|---------------------------------|
| Make/Model | Perkins 404D-22TAG |
| Standby Power | 46.5 hp 31.2 kWe |
| Fuel Consumption - Prime | 8.9 L / Hr 2.35 (US) gal / Hr |
| Fuel Consumption - 50% | 4.6 L / Hr 1.2 (US) gal / Hr |
| Engine Speed | 1800 RPM |
| Number of cylinders | 4 |
| Aspiration | Turbocharged aftercooled |
| Combustion System | Indirect Injection |
| Compression Ratio | 23.3:1 |
| Bore and Stroke | 3.3" x 3.9" |
| Displacement | 2.2 litres 135 in ³ |
| Cooling System | Water Cooled |
| Coolant Capacity | 9.3 L 2.4 gal (US) |
| Oil Capacity | 10.6 L 2.8 gal (US) |
| Oil & Filter Changes | 500 hr dependent on load factor |
| Charging Alternator | 65 amp |
| Starter Battery | 12 Volt 850 cca |
| Warranty | 3000 Hr / 2 Year |

Alternator

| | |
|--------------------|--|
| Model | SM180E |
| Type | Brushless Automatic Voltage Regulated |
| Voltage Regulation | ±1 |
| Rated Output | 125 amps at 240 volts 250 amps at 120 volts |
| Insulation | Class H |
| Warranty | 5 Years |

Fuel Tank

| | |
|----------|-----------------------|
| Volume | 45 Litres / 10 gallon |
| Material | Aluminum |
| Standard | CAN/ULC-S601 |
| Warranty | 5 Year |

Specifications are subject to change without notice.

