



GILLETTE GENERATORS

PORTABLE MODEL

EVTD-65EK-3

60 HERTZ

“EV” SERIES EMERGENCY VEHICLE COMPARTMENT STYLE GEN-SETS

EVTD-65EK (Air Cooled Diesel) is intended for permanent installation into emergency vehicle compartments. These sets are mounted on a “Drip Pan” flat base with pre-mounted vibration isolators and control panel wiring. The “EVTD” models must be mounted by the installer near the diesel fuel source as no fuel tank is provided. All sets must use the vehicle 12 VDC battery for gen-set electric starting power. The gen-set is air-cooled so it must be mounted on a slide-out tray and brought into free cooling air before use.



| SPECIFICATIONS (ALL LISTED ITEMS ARE STANDARD EQUIPMENT ON EACH GEN-SET.) | DIESEL FUEL, THREE PHASE, 60 HERTZ, 208,240 & 480 VOLTS | |
|--|--|--|
| | EVTD-65EK-3 | |
| MAXIMUM KILOWATTS @ 3PH | 6.0 | |
| PRIME KILOWATTS @ 3PH | 5.0 | |
| PRIME AMPS @ 208 V (-3-2) | 18 | |
| PRIME AMPS @ 240 V (-3-3) | 16 | |
| PRIME AMPS @ 480 V (-3-4) | 8 | |
| BRUSHLESS GEN./REG | 5 % VOLTAGE REGULATION FROM NAME PLATE RATING ON ALL POWER-PRO GEN-SETS | |
| FREQUENCY REG | 5% FREQUENCY REGULATION FROM NAMEPLATE RATING ON ALL “EV” SERIES SETS | |
| “KLEEN-POWER”™ | WAVEFORM DISTORTION IS LIMITED TO JUST 7 % ON ALL “EV” GEN-SETS | |
| ENGINE BRAND AND HP AT 3600 RPM. | KOHLER (KD15-440) 9 HP | |
| ENGINE START | ELECTRIC ONLY | |
| ENG. CU. CENTIMETERS | 440 | |
| FULL PRESSURE OIL LUB. | YES | |
| SPIN-ON OIL FILTER | YES | |
| LOW OIL SHUTDOWN | STANDARD ENGINE SHUTDOWN PROTECTION FOR ALL “EV” SERIES SETS | |
| FUEL USE, GAL./HOUR | .52 | |
| FUEL TANK | FUEL TANK IS REMOVED FROM STATIONARY SETS. | |
| CODE G ELECTRIC MOTOR START POWER IN HP RATING | 1 1/2 HP | |
| POWER CONNECTION PANEL COMPONENTS | BLANK PANEL WITH NO RECEPTACLES. A LOAD TERMINAL STRIP IS INCLUDED FOR POWER TAKE-OFF | |
| LENGTH, INCHES | 27 | |
| WIDTH, INCHES. | 20 | |
| HEIGHT, INCHES | 23 | |
| NET WEIGHT, LBS. | 205 | |
| SHIP WEIGHT, LBS. | 222 | |

SPC1-EVTD-65EK-20200812