

ARMAN. GENERATORS

SDG40S-8E1 36 kVA

AIRMAN generators are manufactured to the highest quality, consistently delivering the industry's best return on investment.

ANA is committed to supplying the finest products with unmatched performance and support, maintaining their value over time.

- 36 kVA prime power
- Excellent Fuel Efficiency 24 hour runtime
- Kubota diesel engine
- EPA Tier 4 Final





ANA

Alliance North America

Phone: 562-450-3570 E-mail: sales@anacorp.com

www.anacorp.com

California: 11100 Hope Street • Cypress, CA 90630 Texas: 10440 Brockwood Road • Dallas, Texas 75238 South Carolina: 4220 S. Church St. • Roebuck, SC 29376

© COPYRIGHT 2021, ANA • 010121
AIRMAN is a trademark of HOKUETSU INDUSTRIES CO., LTD.

Features and specifications may change without notice. Please consult ANA for all current information.

SPECIFICATIONS



ARMAN. GENERATORS

SDG40S-8E1 36 kVA

Madal	000400 054	
Model	SDG40S-8E1	
GENERATOR SPECIFICATIONS		
Generator Type	Taiyo Generator End	
Armature Connection	Star with Neutral/Zig Zag	
No. of Poles	4-Pole	
Insulation	F-Class	
Excitation	Brushless with AVR	
Voltage Regulation	±0.5%	
Power Factor %	80	
Frequency	60 Hz	
Prime Power	36 kVA/ 28.8 kW	
Standby Power	37.8 kVA/ 30.2 kW	
Voltage Single Phase	120V / 127V / 139V / 240V / 254V /	
	277V (Switchable)	
Voltage Three Phase	208V / 220V / 240V / 416V / 440V/	
	480V (Switchable)	
AMPERAGE		
Single Phase 120V	108 Amp x 2	
Single Phase 240V	108 Amp	
Three Phase 208V	95 Amp	
Three Phase 240V	86 Amp	
Three Phase 480V	43 Amp	

[000100.001
Model	SDG40S-8E1
ENGINE SPECIFICATIONS	
Engine Model	Kubota V2403-CR-T
EPA Emission Level	Tier 4 Final
Engine Type/Cylinders	4-Cycle, water-cooled, direct injection turbocharged air-to-air intercooled, DOC
Output @ Rated Speed (1800 rpm)	44.9 HP
Governor Type	Electronic
Integral Fuel Tank Capacity	84.5 gal.
Fuel Containment	110%
Lubricating Oil Capacity	2.6 gal.
Coolant Capacity	2.5 gal.
Battery	12V-55Åh x 1
	12 V System
FUEL CONSUMPTION	
FULL Load	2.3 gal./hr.
75% Load	1.7 gal./hr.
50% Load	1.2 gal./hr.
Run Time @ Full Load	36.7 hr.
WEIGHTS AND DIMENSIONS	
LxWxH without Trailer	75" x 38" x 61"
LxWxH with Trailer	144" x 70" x 73"
Trailer Weight	1182 lb.
Dry Weight/Operating	2426 lb. / 3065 lb.
Weight (generator only)	
Sound Level @ 23 Feet	C4/C4 4DA
(No/Full Load)	61/61 dBA



Alliance North America

Phone: 562-450-3570 E-mail: sales@anacorp.com

www.anacorp.com

California: 11100 Hope Street • Cypress, CA 90630 Texas: 10440 Brockwood Road • Dallas, Texas 75238 South Carolina: 4220 S. Church St. • Roebuck, SC 29376