




## XTP120 12KW THREE-PHASE GENERATORS

			
	<b>XTP120EH-208 XTP120EV-208</b>	<b>XTP120EH-240 XTP120EV-240</b>	<b>XTP120EH-480 XTP120EV-480</b>
<b>AC voltage</b>	120/208 Vac	208/240 Vac	277/480 Vac
<b>Max. output</b>	12,000 W	12,000 W	12,000 W
<b>Rated output</b>	11,500 W	11,500 W	11,500 W
<b>Rated current</b>	31.9 A	27.7 A	13.8 A
<b>Current @ .8PF</b>	39.9 A	34.6 A	17.3 A
<b>Output @ .8PF</b>	14,400 kVA	14,400 kVA	14,400 kVA
<b>Starting system</b>	Electric	Electric	Electric
<b>Engine</b>	Honda or Vanguard	Honda or Vanguard	Honda or Vanguard
<b>Displacement</b>	Honda 688 cc Vanguard 627 cc	Honda 688 cc Vanguard 627 cc	Honda 688 cc Vanguard 627 cc
<b>Continuous run time</b>	7.1 hrs. @ 50% load	7.1 hrs. @ 50% load	7.1 hrs. @ 50% load
<b>Fuel capacity</b>	7.25 gal. (27.4L)	7.25 gal. (27.4L)	7.25 gal. (27.4L)
<b>Fuel type</b>	Gasoline	Gasoline	Gasoline
<b>Receptacles</b>	One 120V 20A duplex One 250V 50A straight-blade	One 120V 20A duplex One 120/208V 20A locking	One 480V 20A locking
<b>Dimensions, L x W x H</b>	44¾ x 25¼ x 28¾ in. (114 x 64 x 73cm)	44¾ x 25¼ x 28¾ in. (114 x 64 x 73cm)	44¾ x 25¼ x 28¾ in. (114 x 64 x 73cm)
<b>Dry weight, approx.</b>	330 lbs. (150kg)	330 lbs. (150kg)	330 lbs. (150kg)
<b>Optional accessories</b>	2-wheel kit 4-wheel kit	2-wheel kit 4-wheel kit	2-wheel kit 4-wheel kit
<b>Deratings:</b> Ratings apply for altitudes from sea level up to 1,000 feet (305 meters) with typical cooling, normal ambient temperature and gasoline fuel. Reduce ratings 3.5% for each 1000 feet (305 meters) above sea level and 1.0% for each 10°F rise above 60°F (5.6°C above 15.6°C).			