

AB-SERIES COMPACT BELT-DRIVE GENERATORS

			
	AB30T	AB50	AB60
Voltage	120 Vac	120/240 Vac	120/240 Vac
Frequency	60 Hz	60 Hz	60 Hz
Max. output	3000 W	5000 W	6000 W
Rated output	2400 W	4000 W	5000 W
Rated current	20 A	33.3 A @ 120 V 16.7 A @ 240 V	41.6 A @ 120 V 20.8 A @ 240 V
Shaft diameter	0.875 in. (22mm)	0.875 in. (22mm)	0.875 in. (22mm)
Keyway	0.1875 in. (4.7mm)	0.1875 in. (4.7mm)	0.1875 in. (4.7mm)
Connection	4-wire	4-wire	4-wire
Min. engine power	5 hp	8 hp	11 hp
Min. required torque	7.5 ft lb (10.2 Nm)	12.5 ft lb (16.95 Nm)	16.5 ft lb (22.37 Nm)
Required RPM	3600	3600	3600
Receptacles	One 120Vac 20A duplex	One 120Vac 20A duplex One 240Vac 20A locking	One 120Vac 20A duplex One 240Vac 20A locking
Dimensions, L x W x H	16½ x 8½ x 10½ in. (41 x 22 x 27cm)	14½ x 7¼ x 7½ in. (36 x 18 x 19cm)	15 x 7¼ x 7½ in. (38 x 18 x 19cm)
Dry weight, approx.	40 lbs. (18kg)	42 lbs. (19kg)	49 lbs. (22kg)
Optional accessories	Adapter plate	Adapter plate	Adapter plate